



General description

Hydroseal® Canada 22 CALLIBRE CLEANER is a clear, low VOC emission, water-thin, solvent cleaner. It is specifically formulated to remove grease, oil and dirt from the bonding surfaces of PVC, CPVC, ABS and Styrene tube and fittings. It is approved for Flowguard Gold® CTS plumbing systems.

Application

Hydroseal® Canada 22 CALLIBRE CLEANER is an all purpose cleaner and can be used on all sizes, classes and schedules of PVC, CPVC, ABS and Styrene tube and fittings. It must be used only as a cleaner, in conjunction with the appropriate primer and/or cement combination. Hydroseal® Canada 22 CALLIBRE CLEANER can also be used as a brush cleaner.

Detailed directions on making solvent cemented joints are printed on the container label. An installation DVD/CD covering solvent cementing is available. It not only describes the basic principles of solvent cementing, but also covers the handling, storage and use of our products. It is highly recommended that the installer review the instructions supplied by the tube and fitting manufacturer.

Standards and certification listings



- Meets SCAQMD Rule 1168/316A.
- Compliant with LEED® (Leadership in Energy and Environmental Design). When using this Hydroseal® Canada low VOC product, credit can be claimed for LEED Green Building Rating System – Indoor Environmental Quality.

Specifications

Color: Clear
 Specific Gravity: 0.800 ± 0.04
 Brookfield Viscosity: Water Thin

Shipping:

For One Liter and Above
 Proper Shipping Name: Flammable Liquid
 n.o.s. (Acetone, Methyl Ethyl Ketone)
 Hazard Class: 3
 Identification Number: UN 1993
 Packing Group: II
 Label Required: Flammable Liquid

For Less than One Liter
 Proper Shipping Name: Consumer Commodity Adhesive
 Hazard Class: ORM-D

Directions for use

- Before using this cleaner, tube and fittings should be cut square, deburred and checked for proper fit.
- Use an applicator (e.g. dauber, brush top applicator or paintbrush) at least ½ the size of the tube diameter. Do not use a rag as repeated contact of cleaner-infused rag with skin may cause irritation or blistering.
- Apply 22 CALLIBRE CLEANER freely to the socket keeping surface wet and applicator wet and in motion for 5 - 15 seconds. Be sure to use a scrubbing motion to clean off all grease, oil and dirt. Re-dip if necessary. Avoid puddling the socket.
- Apply 22 CALLIBRE CLEANER to the tube surface in the same manner equal to the depth of the socket.
- Repeat Application to the fitting socket.
- Allow 22 CALLIBRE CLEANER to dry and then apply appropriate Hydroseal® Canada primer and/or cement following instructions on the cans.

Quality assurance

Hydroseal® Canada's 22 CALLIBRE CLEANER is carefully evaluated to assure that consistent high quality is maintained. Fourier transform infrared spectroscopy, gas chromatography, and additional in depth testing ensures each batch is manufactured to exacting standards. A batch identification code is stamped on each can and assures traceability of all materials and processes used in manufacturing this product. The date code of manufacture is stamped on the bottom of the container. Stability of the product is limited by the evaporation of the solvent when the container is opened and not contaminated. Adding of solvents is not recommended and may significantly change the properties of the cleaner.

Availability

PART	SIZE	CLAENER	22 CALLIBRE				
			DESCRIPTION	COLOR	CARTON	N.W(KGS)	G.W (KGS)
0601.922C.0120	4 oz	22 CALLIBRE	CLEAR	24	2.10	3.20	0.29
0601.922C.0250	8 oz			24	4.80	6.00	0.41
0601.922C.0500	16 oz			12	4.80	6.60	0.42
0601.922C.1000	32 oz			12	9.00	12.00	0.78

ACCESSORIES

SAFETY DATA SHEET - 22 CALLIBRE CLEANER FOR PLASTIC TUBE

SECTION

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 22 Callibre Cleaner for Plastic Tube
PRODUCT USE: Low VOC Cleaner for Plastic Tube (PVC, CPVC, ABS and Styrene)
SUPPLIER:
MANUFACTURER: HYDROSEAL CANADA INCORPORATED
 108 West 13th Street. Wilmington, New Castle. Delaware - 19801
 United States of America. Phone: +1-302-298-0822, Fax: +1-302-298-0824
EMERGENCY: Transportation: CHEMTEL Tel. 800.255-3924, 813-248-0585 (International) **Medical:** Tel. 800.451.8346, 760.602.8703 3E Company (International)

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Health		Environmental		Physical	
Acute Toxicity:	Category 4	Acute Toxicity:	None Known	Flammable Liquid	Category 2
Skin Irritation:	Category 3	Chronic Toxicity:	None Known		
Skin Sensitization:	NO				
Eye:	Category 2B				

GHS LABEL:   OR   **Signal Word:** Danger **WHMIS CLASSIFICATION:** CLASS B, DIVISION 2

Hazard Statements	Precautionary Statements
H225: Highly flammable liquid and vapor H319: Causes serious eye irritation H336: May cause drowsiness or dizziness EUH 066: Repeated exposure may cause skin dryness or cracking.	P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking P261: Avoid breathing dust/fume/gas/mist/vapors/spray P280: Wear protective gloves/protective clothing/eye protection/face protection P337+P313: Get medical advice/attention P403+P233: Store in a well ventilated place. Keep container tightly closed P501: Dispose of contents/container in accordance with local regulation

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	EINECS #	REACH Pre-registration Number	CONCENTRATION % by Weight
Methyl Ethyl Ketone (MEK)	78-93-3	201-159-0	05-2116297728-24-0000	4 - 15
Cyclohexanone	108-94-1	203-631-1	05-2116297718-25-0000	2 - 15
Acetone	67-64-1	200-662-2	05-2116297713-35-0000	60 - 90

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.
 * Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).
 # indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 4 - FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.
Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.
Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.
Ingestion: Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media:	Dry chemical powder, carbon dioxide gas, foam, Halon, water fog.			
Unsuitable Extinguishing Media:	Water spray or stream.	Health	2	2
Exposure Hazards:	Inhalation and dermal contact	Flammability	3	3
Combustion Products:	Oxides of carbon and smoke	Reactivity	0	0
Protection for Firefighters:	Self-contained breathing apparatus or full-face positive pressure airline masks.	PPE	B	4-Severe

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: Keep away from heat, sparks and open flame.
 Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.
 Prevent contact with skin or eyes (see section 8).
Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.
Methods for Cleaning up: Clean up with sand or other inert absorbent material. Transfer to a closable steel vessel.
Materials not to be used for clean up: Aluminum or plastic containers

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid breathing of vapor, avoid contact with eyes, skin and clothing.
 Keep away from ignition sources, use only electrically grounded handling equipment and ensure adequate ventilation/fume exhaust hoods.
 Do not eat, drink or smoke while handling.
Storage: Store in ventilated room or shade below 44°C (110°F) and away from direct sunlight.
 Keep away from ignition sources and incompatible materials: caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.
 Follow all precautionary information on container label, product bulletins and solvent cementing literature.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL
	Methyl Ethyl Ketone (MEK)	200 ppm	300 ppm	200 ppm	
	Cyclohexanone	20 ppm	50 ppm	50 ppm	
	Acetone	500 ppm	750 ppm	1000 ppm	

Engineering Controls: Use local exhaust as needed.
Monitoring: Maintain breathing zone airborne concentrations below exposure limits.
Personal Protective Equipment (PPE):
Eye Protection: Avoid contact with eyes, wear splash-proof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as may be appropriate for the exposure.
Skin Protection: Prevent contact with the skin as much as possible. Butyl rubber gloves should be used for frequent immersion.
 Use of solvent-resistant gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.
Respiratory Protection: Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes.
 Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above. With normal use, the Exposure Limit Value will not usually be reached.
 When limits approached, use respiratory protection equipment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear, thin liquid	Odor Threshold:	0.88 ppm (Cyclohexanone)
Odor:	Ketone	Boiling Range:	56°C (133°F) to 156°C (313°F)
pH:	Not Applicable	Evaporation Rate:	> 1.0 (BUAC = 1)
Melting/Freezing Point:	-95°C (-139°F) Based on first melting component: Acetone	Flammability:	Category 2
Boiling Point:	56°C (133°F) Based on first boiling component: Acetone	Flammability Limits:	LEL: 1.1% based on Cyclohexanone UEL: 12.8% based on Acetone
Flash Point:	-20°C (-4°F) T.C.C. based on Acetone	Vapor Pressure:	190 mm Hg @ 20°C (68°F): Acetone
Specific Gravity:	0.795 @ 23°C (73°F)	Vapor Density:	>2.0 (Air = 1)
Solubility:	Solvent portion soluble in water.	Other Data: Viscosity:	Water-thin
Partition Coefficient n-octanol/water:	Not Available		
Auto-ignition Temperature:	465°C (869°F): Acetone		
Decomposition Temperature:	Not Applicable		
VOC Content:	When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: <= 550 g/l.		

SECTION 10 - STABILITY AND REACTIVITY

Stability:	Stable
Hazardous decomposition products:	None in normal use. When forced to burn, this product gives off oxides of carbon and smoke.
Conditions to avoid:	Keep away from heat, sparks, open flame and other ignition sources.
Incompatible Materials:	Oxidizers, strong acids and bases, amines, ammonia

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Inhalation, Eye and Skin Contact
Acute symptoms and effects:	Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.
Inhalation:	Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid.
Eye Contact:	Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.
Skin Contact:	May cause nausea, vomiting, diarrhea and mental sluggishness.
Ingestion:	None known to humans
Chronic (long-term) effects:	LD ₅₀
Toxicity:	Oral: 2737 mg/kg (rat), Dermal: 6480 mg/kg (rabbit)
Methyl Ethyl Ketone (MEK)	LC ₅₀ Inhalation 8 hrs. 23,500 mg/m ³ (rat)
Cyclohexanone	Inhalation 4 hrs. 8,000 PPM (rat)
Acetone	Inhalation 50,100 mg/m ³ (rat)

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:	None Known
Mobility:	In normal use, emission of volatile organic compounds (VOC's) to the air takes place, typically at a rate of <= 550 g/l.
Degradability:	Biodegradable
Bioaccumulation:	Minimal to none.

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.

SECTION 14 - TRANSPORT INFORMATION

Proper Shipping Name:	Flammable Liquid, n.o.s. (Acetone, Methyl Ethyl Ketone)
Hazard Class:	3
Secondary Risk:	None
Identification Number:	UN 1993
Packing Group:	PG II
Label Required:	Class 3 Flammable Liquid
Marine Pollutant:	NO

EXCEPTION for Ground Shipping	
DOT Limited Quantity	Up to 1L per inner packaging, 30 kg gross weight per package.
Consumer Commodity:	Depending on packaging, these quantities may qualify under DOT as "ORM-D".
TDG INFORMATION	
TDG CLASS:	FLAMMABLE LIQUID 3
SHIPPING NAME:	Flammable Liquid, n.o.s. (Acetone, Methyl Ethyl Ketone)
UN NUMBER/PACKING GROUP:	UN 1993, PG II

SECTION 15 - REGULATORY INFORMATION

Precautionary Label Information:	Highly Flammable, Irritant	Ingredient Listings: USA TSCA, Europe EINECS, Canada DSL, Australia AICS, Korea ECL/TCCL, Japan MITI (ENCS)
Symbols:	F, Xi	
Risk Phrases:	R11: Highly flammable. R36/37: Irritating to eyes and respiratory system.	R66: Repeated exposure may cause skin dryness or cracking. R67: Vapors may cause drowsiness and dizziness.
Safety Phrases:	S2: Keep out of the reach of children. S9: Keep container in a well-ventilated place. S16: Keep away from sources of ignition - No smoking.	S25: Avoid contact with eyes. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S33: Take precautionary measures against static discharges.

SECTION 16 - OTHER INFORMATION

Specification Information:		
Department issuing data sheet:	Hydroséal Laboratories	
E-mail address:	info@hydroséal.ca	All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).
Training necessary:	Yes, training in practices and procedures contained in product literature.	
Reissue date / reason for reissue:	12/14/2011 / Updated GHS Standard Format	
Intended Use of Product:	Cleaner for Plastic Tube (PVC, CPVC, ABS and Styrene)	

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.